

Vitascan v.2 probe

VitaScan v.2 probe is accurate and easy to use, utilizing **BladderVue™** for reliable results. Single-button control to start/stop the bladder scanning. Fully automated 3D scanning within seconds. No sonographical experience is needed.

Features

BladderVue™ integrated

Enhanced Bladder Detection Technology

Robust and Accurate 3D probe

Drop tested according IEC 60601-1

Vitascan application

Installed on multiple devices for easy access

Free Software upgrades

Tutorial

Optional

Soft carrying case

Accurate scan result using **BladderVue™** technology.

Flexible add-on solution for Computer on Wheels.



Optimize use

- No routine calibration needed
- Probe Verification Software
- Free software updates
- USB-C or USB-A options
- On-line learning hub for operators
- 2 years warranty
- Optional service contracts
- Optional extended warranty contracts

Weight & dimensions

Probe: 380 g 18.5 x 4.5 x 4.5 cm

Technical specification

Volume range	0 - 1000 mL
Accuracy	+/- 7,5%* on volumes greater than 100 mL +/- 7,5* mL on volumes less than 100 mL
Probe frequency	3.45 MHz
Scanning method	Sector, 180 degrees
Rotation positions	12 or 24 rotating positions
Sweep angle	130 degrees
Wi-Fi connectivity	Yes
Drop test	ISO 60601 - 1 standard, 15.3.4.1
Input voltage	100 - 240VAC, 50 - 60Hz



*Vitascan v.2 used with stated instructions, using a Vitacon tissue-equivalent phantom.